

Dela-Fit is a unique system of quick fitting nozzles of various spray types which allows connection to pipework without the use of spanners.

<b>Nozzle Type</b>	<b>Spray Characteristics</b>	<b>Spray Angles</b>	<b>Basic Features</b>	<b>Flow Range. L/Min @ 3 Bar.G.</b>	<b>Page No.</b>
DFAC	Uniform flat spray pattern with tapered edges.	0° – 90°	Standard and large nozzles with 'chamfaloc' locking mechanism.	3,93 – 79,07	G.1
DFAN	Wide angle deflected flat spray with relatively uniform distribution.	120° Nom.	Standard and large nozzles with 'chamfaloc' locking mechanism.	3,94 – 78,9	G.2
DFAE	Uniformly distributed hollow cone spray with fine to coarse atomisation.	70°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,4 – 79,0	G.3
DFAF	Uniformly distributed hollow cone spray with fine to coarse atomisation.	110°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,4 – 79,0	G.4
DFTJ	Evenly distributed deflected flat spray for low pressure impact cleaning.	35°, 40°, 50°	Standard and large nozzles with 'chamfaloc' locking mechanism.	3,9 – 39	G.5
DFBI	Uniformly distributed solid cone spray with fine to coarse atomisation.	47° – 86°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,65 – 28,89	G.6
DFBN	Uniformly distributed solid cone spray with fine to coarse atomisation.	85° – 128°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,65 – 26,06	G.7
DFBQ	Uniformly distributed solid cone spray with fine to coarse atomisation.	47° – 86°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,65 – 28,89	G.8
DFBT	Uniformly distributed solid cone spray with fine to coarse atomisation.	85° – 128°	Standard and large nozzles with 'chamfaloc' locking mechanism.	2,65 – 26,06	G.9
DF BODIES	–	–	Standard and large mating bodies for nozzles with 'chamfaloc' locking mechanism.	–	G.10
AD ADAPTORS	–	–	Standard and large adaptors to fit Dela-Fit bodies to enable threaded nozzles to be used.	–	G.10
FB CAPS BODIES	–	–	Mating bodies and caps with 'chamfaloc' locking mechanism for use with standard flanged nozzles.	–	G.11
SEALS	–	–	EPDM and Viton seals for standard and large Dela-Fit bodies and FB caps.	–	G.11

DELA-FIT

Contact our Helpline for any special requirements:  
Tel: +44 (0) 151 424 6821  
Fax: +44 (0) 151 495 1043  
e-mail:sales@delavan.co.uk  
Web:www.delavan.co.uk