

TYPE TZ-82F

SPECIFICATIONS

Materials

AISI 316L, PTFE, Carbon, Tefzel

Max. working temperature

95 °C (203 °F)

Weight

8,5 kgs (18,7 lbs) fixed model

Max. throw length

18-31 m (59-102 ft.)

Lubricant

Self-lubricating with the cleaning fluid

Installation

Fixed

Working pressure

2-12 Bar (30-174 psi)

Flange

ø127 - PC98.5 - 4 ø11 mm (0,43") holes

Recommended pressure

5-10 Bar (72-145 psi)

TYPE TZ-65

SPECIFICATIONS

Materials

Bronze, AISI 316L, PTFE, PVDF, Carbon

Max. throw length

22-36 m (72-118 ft.)

Weight

15 kgs (33 lbs) portable model

16 kgs (35,3 lbs) fixed model

Installation

Fixed or portable

Lubricant

Self-lubricating with the cleaning fluid

Standard thread

2" NPT or 2½" ASA for portable installation

Working pressure

2-12 Bar (30-174 psi)

Flange

ø165 - PC125 - 4 x ø19 mm (0,75") holes

Recommended pressure

5-10 Bar (72-145 psi)

Max. working temperature

95 °C (203 °F)

TYPE TZ-75

SPECIFICATIONS

Materials

AISI 316L, AISI 316, PTFE, Carbon, PEEK, Tefzel

Max. working temperature

95 °C (203 °F)

Weight

13 kgs (28,7 lbs) portable model

16 kgs (35,3 lbs) fixed model

Max. throw length

22-36 m (72-118 ft.)

Lubricant

Self-lubricating with the cleaning fluid

Installation

Fixed or portable

Working pressure

2-12 Bar (30-174 psi)

Standard thread

2" NPT 2½" ASA for portable installation

Recommended pressure

5-10 Bar (72-145 psi)

Flange

ø127 - PC98.5 - 4 x ø11 mm (0,43") holes

Contact Delavan's Customer Service Team for further details.

CLEANING IN PLACE

TYPE TZ-82F/65/75

Contact our Helpline for any special requirements:
Tel: +44 (0) 151 424 6821
Fax: +44 (0) 151 495 1043
e-mail: sales@delavan.co.uk
Web: www.delavan.co.uk

