

TURNATIP KIT

AIRLESS



FEATURES

- The Turnatip Kit utilises the same Carbide insert as the Airless Tip but with a Brass housing to fit a Turnaflo adaptor.
- The Brass housing is bonded to the Carbide insert and is slotted in the orifice area. The slot is also utilised for orientation purposes by using a special alignment tool.
- Each Turnatip Kit is supplied with grubscrews, for both Delavan and competitive units, and an alignment tool.
- The Turnatip number is stamped on the Brass housing for ease of identification e.g.D2.
- The Turnatip is flow tested and pattern width checked in the same way as the Airless Tip.

TURNATIP KIT CONTENTS

- Turnatip size as per order.
- W00126 - Hardened Steel safety grubscrews for use with Turnaflo.
- W00127 - Hardened Steel safety grubscrews for use with competitive units.
- W00761 - Turnatip alignment tool.

ORDER EXAMPLE

Turnatip Kit P4.

| TURNATIP NUMBER | AIRLESS TIP REF. | EQUIV. ORIFICE (INCHES) | PATTERN WIDTH (INCHES) | FLOW RATE* |
|-----------------|------------------|-------------------------|------------------------|------------|
| X-2 | C515 | | 3 | |
| X-3 | C525 | 0,005 | 5 | 0,02 |
| X-4 | C540 | | 7 | |
| A-2 | C715 | | 3 | |
| A-3 | C725 | 0,007 | 5 | 0,4 |
| A-4 | C735 | | 6 | |
| A-5 | C740 | | 7 | |
| B-2 | C915 | | 3 | |
| B-3 | C925 | | 5,5 | |
| B-4 | C940 | 0,009 | 7 | 0,06 |
| B-5 | C950 | | 8,5 | |
| B-6 | C965 | | 10 | |
| C-2 | C1115 | | 3 | |
| C-3 | C1125 | | 5,5 | |
| C-4 | C1140 | 0,011 | 7 | 0,08 |
| C-5 | C1150 | | 8,5 | |
| C-6 | C1165 | | 10 | |
| C-7 | C1180 | | 11,5 | |
| D-2 | C1315 | | 3 | |
| D-3 | C1325 | | 5,5 | |
| D-4 | C1340 | | 8 | |
| D-5 | C1350 | 0,013 | 9 | 0,12 |
| D-6 | C1365 | | 11 | |
| D-7 | C1380 | | 13 | |
| D-8 | C1395 | | 14 | |
| E-2 | C1515 | | 4 | |
| E-3 | C1525 | | 6 | |
| E-4 | C1540 | | 8 | |
| E-5 | C1550 | 0,015 | 10 | 0,16 |
| E-6 | C1565 | | 12 | |
| E-7 | C1580 | | 14 | |
| E-8 | C1595 | | 15,5 | |
| F-2 | C1615 | | 4 | |
| F-3 | C1625 | 0,016 | 6 | 0,19 |
| F-4 | C1640 | | 8 | |
| F-5 | C1650 | | 10 | |

| TURNATIP NUMBER | AIRLESS TIP REF. | EQUIV. ORIFICE (INCHES) | PATTERN WIDTH (INCHES) | FLOW RATE* |
|-----------------|------------------|-------------------------|------------------------|------------|
| F-6 | C1665 | | 12 | |
| F-7 | C1673 | 0,016 | 14 | 0,19 |
| F-8 | C1680 | | 15 | |
| F-9 | C1695 | | 17 | |
| G-2 | C1825 | | 6 | |
| G-3 | C1840 | | 8,5 | |
| G-4 | C1850 | 0,018 | 10 | 0,25 |
| G-5 | C1865 | | 13 | |
| G-6 | C1880 | | 15 | |
| G-7 | C1895 | | 17 | |
| H-2 | C2025 | | 6 | |
| H-3 | C2040 | | 8,5 | |
| H-4 | C2050 | | 10 | |
| H-5 | C2060 | 0,020 | 12 | 0,28 |
| H-6 | C2065 | | 14 | |
| H-7 | C2080 | | 16 | |
| H-8 | C2095 | | 18 | |
| J-2 | C2125 | | 6 | |
| J-3 | C2140 | | 8,5 | |
| J-4 | C2150 | 0,021 | 11,5 | 0,33 |
| J-5 | C2165 | | 15 | |
| J-6 | C2180 | | 17 | |
| J-7 | C2195 | | 19 | |
| K-2 | C2425 | | 7 | |
| K-3 | C2440 | | 9 | |
| K-4 | C2450 | | 12 | |
| K-5 | C2465 | 0,024 | 15 | 0,42 |
| K-6 | C2473 | | 17 | |
| K-7 | C2480 | | 18,5 | |
| K-8 | C2495 | | 21 | |
| L-2 | C2625 | | 7 | |
| L-3 | C2640 | | 9 | |
| L-4 | C2650 | 0,026 | 12 | 0,50 |
| L-5 | C2665 | | 15 | |
| L-6 | C2680 | | 18,5 | |
| L-7 | C2695 | | 21 | |

| TURNATIP NUMBER | AIRLESS TIP REF. | EQUIV. ORIFICE (INCHES) | PATTERN WIDTH (INCHES) | FLOW RATE* |
|-----------------|------------------|-------------------------|------------------------|------------|
| M-2 | C2925 | | 7 | |
| M-3 | C2940 | | 9 | |
| M-4 | C2950 | | 12 | |
| M-5 | C2965 | 0,029 | 15 | 0,63 |
| M-6 | C2973 | | 17 | |
| M-7 | C2980 | | 18,5 | |
| M-8 | C2995 | | 21,5 | |
| N-2 | C3140 | | 9 | |
| N-3 | C3150 | | 12 | |
| N-4 | C3165 | 0,031 | 15 | 0,75 |
| N-5 | C3180 | | 18,5 | |
| N-6 | C3195 | | 21,5 | |
| P-2 | C3640 | | 9 | |
| P-3 | C3650 | | 12 | |
| P-4 | C3665 | 0,036 | 15 | 1,0 |
| P-5 | C3680 | | 18,5 | |
| P-6 | C3695 | | 21,5 | |
| P-7 | C36110 | | 24 | |
| R-2 | C4195 | 0,041 | 21,5 | 1,2 |
| R-3 | C4340 | | 9 | |
| R-4 | C4350 | | 12 | |
| R-5 | C4365 | 0,043 | 15 | 1,5 |
| R-6 | C4380 | | 18,5 | |
| R-7 | C4395 | | 21,5 | |
| S-2 | C4880 | 0,048 | 18,5 | 1,7 |
| S-3 | C4895 | | 22 | |
| T-2 | C5240 | 0,052 | 9 | 2,0 |
| T-3 | C5265 | | 15 | |
| V-3 | C6240 | 0,062 | 9 | 3,0 |
| V-4 | C6265 | | 15 | |
| W-2 | C7265 | 0,072 | 15 | 4,0 |
| W-3 | C8565 | 0,085 | 15 | 5,7 |

* Flow rates are indicated in US gallons/min (water) at an operating pressure of 1000 PSIG (69 Bar.G.).

Contact our Helpline for any special requirements:
Tel: +44 (0) 151 424 6821
Fax: +44 (0) 151 495 1043
e-mail: sales@delavan.co.uk
Web: www.delavan.co.uk

